


Resistor Colour Codes



Tolerance and TCR Codes

Tolerance Codes

B = 0.1% G = 2%
 C = 0.25% J = 5%
 D = 0.5% K = 10%
 F = 1% M = 20%

TCR Codes

±15ppm/°C = A
 ±25ppm/°C = E
 ±50ppm/°C = F
 ±100ppm/°C = S
 ±200ppm/°C = L

ARCOL UK Limited,
 Threemilestone Ind. Estate,
 Truro, Cornwall, TR4 9LG, UK.
 T +44 (0) 1872 277431
 F +44 (0) 1872 222002
 E sales@arcolresistors.com

www.arcolresistors.com

Resistor Preferred Range

E6	E12	E24	E96	E6	E12	E24	E96
10	10	10	10.0				31.6
			10.2				32.4
			10.5	33	33	33	33.2
			10.7				34.0
		11	11.0				34.8
			11.3				35.7
			11.5			36	36.5
			11.8				37.4
	12	12	12.1				38.3
			12.4				39.2
			12.7				40.2
		13	13.0				41.2
			13.3				42.2
			13.7			43	43.2
			14.0				44.2
			14.3				45.3
			14.7				46.4
15	15	15	15.0	47	47	47	47.5
			15.4				48.7
			15.8				49.9
		16	16.2			51	51.1
			16.5				52.3
			16.9				53.6
			17.4				54.9
			17.8		56	56	56.2
	18	18	18.2				57.6
			18.7				59.0
			19.1				60.4
			19.6			62	61.9
		20	20.0				63.4
			20.5				64.9
			21.0				66.5
			21.5	68	68	68	68.1
22	22	22	22.1				69.8
			22.6				71.5
			23.2				73.2
			23.7			75	75.0
		24	24.3				76.8
			24.9				78.7
			25.5				80.6
			26.1				82.5
			26.7	82	82	82	84.5
	27	27	27.4				86.6
			28.0				88.7
			28.7			91	90.9
			29.4				93.1
		30	30.1				95.3
			30.9				97.6

Above values are in accordance with BS2488